

## AUSTROFLAMM ELISABETH

Calor eficiente y diseño sofisticado: Austroflamm Elisabeth con piedra natural, sistema estanco y alto rendimiento.



[Ver más información online](#)

ELISABETH



www

SALVADOR

or.com



[www.austroflamm.com](http://www.austroflamm.com)

| Dimensions and weight                                          |                   |
|----------------------------------------------------------------|-------------------|
| Height [mm]                                                    | 1200              |
| Width [mm]                                                     | 550               |
| Depth [mm]                                                     | 516               |
| Combustion chamber width [mm]                                  | -                 |
| Combustion chamber height [mm]                                 | -                 |
| Combustion chamber depth [mm]                                  | -                 |
| Baking compartment width [mm]                                  | -                 |
| Baking compartment height [mm]                                 | -                 |
| Baking compartment depth [mm]                                  | -                 |
| Warming drawer, width [mm]                                     | -                 |
| Warming compartment height [mm]                                | -                 |
| Warming drawer, depth [mm]                                     | -                 |
| Dimensions, a (with Austroflamm elbow piece) [mm]              | -                 |
| Dimensions, b (with Austroflamm elbow piece) [mm]              | -                 |
| Dimensions, c (with Austroflamm elbow piece) [mm]              | -                 |
| Dimensions, d (with Austroflamm elbow piece) [mm]              | -                 |
| Flue pipe outlet, diameter [mm]                                | 130               |
| Outside air connection diameter [Ø mm]                         | 125               |
| Weight, basic appliance [kg]                                   | -                 |
| Weight Xtra [kg]                                               | -                 |
| Weight, HMS [kg]                                               | -                 |
| Total weight inc. steel case (STM) [kg]                        | -                 |
| Total weight inc. ceramic case (KGM) [kg]                      | -                 |
| Total weight inc. soapstone case (SPM) [kg]                    | -                 |
| a: Safety distance to combustible materials, front [mm]        | under examination |
| b: Safety distance to combustible materials, left [mm]         | under examination |
| c: Safety distance to combustible materials, rear [mm]         | under examination |
| d: Safety distance to combustible materials, right [mm]        | under examination |
| Safety distance to combustible materials, floor [mm]           | under examination |
| Minimum distance from non-flammable materials [mm]             | 50                |
| Output                                                         |                   |
| Nominal heat efficiency [kW]                                   | under examination |
| Minimum heat output [kW]                                       | under examination |
| Maximum heat output [kW]                                       | under examination |
| Minimum room heating capacity [m³]                             | under examination |
| Maximum room heating capacity [m³]                             | under examination |
| Energy efficiency class                                        | under examination |
| Equipment                                                      |                   |
| Xtra heat storage technology                                   | -                 |
| Heat Memory System                                             | -                 |
| External air connection / operation independent of ambient air | -                 |
| Ash removal                                                    | Ash box           |
| Data for the chimney sweep                                     |                   |
| Exhaust gas mass flow [g/s]                                    | under examination |
| Flue gas temperature [°C]                                      | under examination |
| Minimum delivery pressure at nominal heat output [Pa]          | under examination |
| at 0.8 times nominal heat output [Pa]                          | under examination |