

## AUSTROFLAMM ELISE

Estufa Elise: 7?kW, revestimiento en piedra natural, interior Keramott y cristal panorámico. Estilo y eficiencia para tu hogar.



[Ver más información online](#)

ELISE



[www.austroflamm.com](http://www.austroflamm.com)

## Dimensions and weight

|                                                         |                   |
|---------------------------------------------------------|-------------------|
| Height [mm]                                             | 1046              |
| Width [mm]                                              | 550               |
| Depth [mm]                                              | 516               |
| Combustion chamber width [mm]                           | -                 |
| Combustion chamber height [mm]                          | -                 |
| Combustion chamber depth [mm]                           | -                 |
| Baking compartment width [mm]                           | -                 |
| Baking compartment height [mm]                          | -                 |
| Baking compartment depth [mm]                           | -                 |
| Warming drawer, width [mm]                              | -                 |
| Warming compartment height [mm]                         | -                 |
| Warming drawer, depth [mm]                              | -                 |
| Dimensions, a (with Austroflamm elbow piece) [mm]       | -                 |
| Dimensions, b (with Austroflamm elbow piece) [mm]       | -                 |
| Dimensions, c (with Austroflamm elbow piece) [mm]       | -                 |
| Dimensions, d (with Austroflamm elbow piece) [mm]       | -                 |
| Flue pipe outlet, diameter [mm]                         | 130               |
| Outside air connection diameter [Ø mm]                  | 125               |
| Weight, basic appliance [kg]                            | -                 |
| Weight Xtra [kg]                                        | -                 |
| Weight, HMS [kg]                                        | -                 |
| Total weight inc. steel case (STM) [kg]                 | -                 |
| Total weight inc. ceramic case (KGM) [kg]               | -                 |
| Total weight inc. soapstone case (SPM) [kg]             | -                 |
| a: Safety distance to combustible materials, front [mm] | under examination |
| b: Safety distance to combustible materials, left [mm]  | under examination |
| c: Safety distance to combustible materials, rear [mm]  | under examination |
| d: Safety distance to combustible materials, right [mm] | under examination |
| Safety distance to combustible materials, floor [mm]    | under examination |
| Minimum distance from non-flammable materials [mm]      | 50                |

## Output

|                                    |                   |
|------------------------------------|-------------------|
| Nominal heat efficiency [kW]       | under examination |
| Minimum heat output [kW]           | under examination |
| Maximum heat output [kW]           | under examination |
| Minimum room heating capacity [m³] | under examination |
| Maximum room heating capacity [m³] | under examination |
| Energy efficiency class            | under examination |

## Equipment

|                                                                |         |
|----------------------------------------------------------------|---------|
| Xtra heat storage technology                                   | -       |
| Heat Memory System                                             | -       |
| External air connection / operation independent of ambient air | -       |
| Ash removal                                                    | Ash box |

## Data for the chimney sweep

|                                                       |                   |
|-------------------------------------------------------|-------------------|
| Exhaust gas mass flow [g/s]                           | under examination |
| Flue gas temperature [°C]                             | under examination |
| Minimum delivery pressure at nominal heat output [Pa] | under examination |
| at 0.8 times nominal heat output [Pa]                 | under examination |