




www.forjas-salvador.com

IVY



AUSTROFLAMM



www.austroflamm.com

Dimensions and weight

Height [mm]	1143
Width [mm]	400
Depth [mm]	400
Combustion chamber width [mm]	292
Combustion chamber height [mm]	439
Combustion chamber depth [mm]	225
Baking compartment width [mm]	-
Baking compartment height [mm]	-
Baking compartment depth [mm]	-
Warming drawer, width [mm]	-
Warming compartment height [mm]	-
Warming drawer, depth [mm]	-
Dimensions, a (with Austroflamm elbow piece) [mm]	1240
Dimensions, b (with Austroflamm elbow piece) [mm]	1055
Dimensions, c (with Austroflamm elbow piece) [mm]	313
Dimensions, d (with Austroflamm elbow piece) [mm]	200
Flue pipe outlet, diameter [mm]	130
Outside air connection diameter [Ø mm]	125
Weight, basic appliance [kg]	124
Weight Xtra [kg]	-
Weight, HMS [kg]	43
Total weight inc. steel case (STM) [kg]	124
Total weight inc. ceramic case (KGM) [kg]	-
Total weight inc. soapstone case (SPM) [kg]	-
dP Radiation front [mm]	1000
dS1 Distance left [mm]	750
dR Distance rear [mm]	200
dS2 Distance right [mm]	750
dB Distance bottom [mm]	0
Minimum distance from non-flammable materials [mm]	50

Output

Nominal heat efficiency [kW]	5.0
Minimum heat output [kW]	2.5
Maximum heat output [kW]	7.0
Minimum room heating capacity [m³]	48
Maximum room heating capacity [m³]	124
Energy efficiency class	A+

Equipment

Xtra heat storage technology	-
Heat Memory System	Accessories
External air connection / operation independent of ambient air	Yes
Ash removal	Ash box

Data for the chimney sweep

Exhaust gas mass flow [g/s]	4.2
Flue gas temperature [°C]	263
Minimum delivery pressure at nominal heat output [Pa]	12
at 0.8 times nominal heat output [Pa]	10